

## MC-Series : MC-804II/MC-1204II/MC-1604II

### FEATURES :

- MC-804II : 8-Mic/Line inputs, MC-1204II : 12-Mic/Line inputs, MC-1604II : 16-Mic/Line inputs
- 3-Aux including pre/post fader configurability
- 3-band EQ with swept on Mic/Line Ins, PFL Solo
- 4-Bus Structures with 2 subgroup outs
- 4-Stereo inputs for effect units or stereo instruments
- 100mm tapered faders throughout
- +48V Phantom Power for condenser Mics
- Channel and Mix Inserts, 12 segment tri-colored metering
- Dedicated Mono Sum Output
- Include Rack Mounting (MC-804II Only)



### APPLICATIONS :

#### STUDIO RECORDING

- Digital and analogue multitrack setups
- Small studios
- Home studios
- Pre-production suites

#### Video post production suites

#### LIVE SOUND

- Bands
- Small venues
- Clubs
- Conferences
- Schools
- Places of worship

### Specifications : MC-Series

	MC-804II	MC-1204II	MC-1604II
Frequency Response MIC input to any output LINE input to any output STEREO input to any output		Min 15Hz-30kHz +/-1dB, Max 40Hz-30kHz +/-1dB Min 10Hz-20kHz +/-1dB, Max 40Hz-20kHz +/-1dB Min 10Hz-20kHz +/-1dB, Max 20Hz-20kHz +/-1dB	
MIC/LINE HPF Channel Equalizer		100Hz-18dB/Octave LF 100Hz +/-12dB Shelving, HF 10kHz +/-12dB Shelving MF 350Hz-5kHz +/-12dB peaking (MIC/LINE channel only)	
Crosstalk ref 20dBu Channel off Fader Routing Isolation AUX Send Pots offness		>86dB @1kHz, 70dB @20kHz >83dB @1kHz, 70dB @20kHz >65dB @1kHz, 65dB @20kHz >90dB @1kHz, 70dB @20kHz	
THD+N% 20Hz-20kHz		<0.02% Any output @1kHz 20dBu	
CMRR MIC/LINE input STEREO input EIN 20Hz-20kHz 150Ω MIC/LINE input STEREO input		>60dB/40dB >40dB <-127dBu <-95dBu	
Gain ref Mix/Sub output Mic input Line input Stereo input Rec output Aux, Monitor, Mono		21dB to 70dB 1dB to 50dB 4dB to 28dB -14dB +3dB	
Input & Output Impedance Mic input Line input Stereo/Return input Track input Any output		3kΩ Balanced 10kΩ Balanced 30kΩ Balanced 30kΩ Unbalanced 75Ω	
Input & Output Max Level Mic input Line input Stereo input Any Audio output Headphone		12dBu 32dBu 28dBu 20dBu 150mW @200Ω	
Dimensions (WxHxD)	469x440x101mm	469x578x101mm	469x706x101mm
Weight	9.2kg/20.2lbs	9.5kg/20.9lbs	10.36kg/22.8lbs

All features & specifications subject to change without notice. ©NPE Industry (Thailand) Co.,Ltd March 2008

<http://www.myNPE.com>

Distributor :

E-Mail: [myNPE@myNPE.com](mailto:myNPE@myNPE.com)

**บริษัท นัทพงษ์ เซลส์แอนด์เซอร์วิส จำกัด**  
**Natthapong Sales & Service Co.,Ltd.**

สำนักงานใหญ่ : 119,119/1 ถนนอโศกวิภาวดี วิศวกรรมศาสตร์ พระนคร กรุงเทพฯ 10200  
โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020  
สาขาศูนย์วิจัย : ชั้น G (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ด.จตุจักร อ.จตุจักร ก.ปทุมธานี 12130 โทรศัพท์ : 0-2992-7379 โทรสาร : 0-2992-7380

<http://www.mynpe.com> E-Mail: [mynpe@mynpe.com](mailto:mynpe@mynpe.com)