

Specifications :

PDA-100

Power Output at 1 kHz	100 Watts
Distortion (THD) : @ 1kHz 4 Ω	< 2 %
Frequency Response : 0,-3 dB	
Line	50 Hz-15 kHz
Horn	150 Hz-15 kHz
Input Sensitivity	
MIC	-50 dBu
AUX-TAPE	-25 dBu
AMP IN	0 dBu
Input Impedance	
MIC	> 2 kΩ
AUX-TAPE	> 12 kΩ
AMP IN	> 50 kΩ
Line Output	4,8,16 Ω
70 v	100 Ω
100 v	200 Ω
Tone Control	
Low +/-10dB	100 Hz
High +/-10dB	10 kHz
Power Supply	220 V 50/60 Hz 12 VDC
Dimensions (W x H x D)	483 x 88 x 380 mm
Weight	10.9 kg/23.98 lbs

Specifications :

PDA-150

Power Output at 1 kHz	150 Watts
Distortion (THD) : @ 1kHz 4 Ω	< 2 %
Frequency Response : 0,-3 dB	
Line	50 Hz-15 kHz
Horn	150 Hz-15 kHz
Input Sensitivity	
MIC	-50 dBu
AUX-TAPE	-25 dBu
AMP IN	0 dBu
Input Impedance	
MIC	> 2 kΩ
AUX-TAPE	> 12 kΩ
AMP IN	> 50 kΩ
Line Output	4,8,16 Ω
70 v	50 Ω
100 v	100 Ω
Tone Control	
Low +/-10dB	100 Hz
High +/-10dB	10 kHz
Power Supply	220 V 50/60 Hz 12 VDC
Dimensions (W x H x D)	483 x 88 x 380 mm
Weight	12.5 kg/45.1 lbs

PDA-Series



Specifications :

PDA-300

PDA-400

PDA-550

Frequency Response @ Pre output	Mixer Section 50Hz-20kHz 0,-2dB 50Hz-20kHz 0,-2dB 50Hz-20kHz 0,-2dB HPF 150 Hz Roll 6dB		
Mic Input AUX Input Return Input Horn Mode			
Distortion (THD) Frequency 1kHz	max all outputs Master Equalizer +/- 10dB		
Noise Measured 20 Hz-20kHz	Mic Input Ref 150 Ω -120dBu		
Equivalence Input noise	AUX Input -110dBu		
Gain	Mic Input Ref 150 Ω 50 dB Line Input 24 dB Return Input 18 dB		
Maximum Input Level (min gain)	Mic Input 14 dBV Line Input 6 dBV Return Input 8 dBV		
Input Impedance	Mic Input >2kΩ		
All Unbalanced Inputs	Line Input >12kΩ Return Input >3kΩ		
Power Amplifier -Input Sensitivity	0dBV	0dBV	0dBV
Input Impedance	>50kΩ	>50kΩ	>50kΩ
Frequency Response All Output	50Hz-12kHz+/-1dB	50Hz-12kHz+/-1dB	50Hz-12kHz+/-1dB
Matching Output System	4,8,16,ohms70,100 volt	4,8,16,ohms70,100 volt	4,8,16,ohms70,100 volt
Power Rating All Output	Max 300 watts rms	Max 400 watts rms	Max 550 watts rms
Distortion (THD)	Better Than 1%	Better Than 2%	Better Than 2%
Frequency 1kHz before ripple			
Noise Measured 20Hz-20kHz @ 8Ω	-60dBu	-60dBu	-60dBu
AC & DC IN Fuse	Yes	Yes	Yes
Power Requirement	AC 220V & DC 12 V	AC 220V & DC 24 V	AC 220V & DC 24 V
Dimensions Width x Height x Depth (Exclude knobs & connector)	482.6 x 133 x 455mm	482.6 x 133 x 455mm	482.6 x 133 x 455mm
Pack Carton	21"x9"x22" 3/4"	21"x9"x22" 3/4"	21"x9"x22" 3/4"
Weight kgs/lbs (Exclude pack carton)	20.5/45.1lbs	21/46.2 lbs	29.0/63.8 lbs

All features & specifications subject to change without notice. ©NPE Industry (Thailand) Co.,Ltd February 2010

Note : 0dBu=0.775Vrms, 0dBV=1Vrms

Distributor :

www.myNPE.com E-Mail: myNPE@myNPE.com

บริษัท บัวทอง เซลส์แอนด์เซอร์วิส จำกัด
Natthapong Sales & Service Co.,Ltd.

สำนักงานใหญ่ : 119,119/1 ถนนอโศกวงค์ 5 แขวงพญาภิรมย์ พระนคร กรุงเทพฯ 10200
 โทรศัพท์ : 0-2225-0094, 0-2623-8899 (อัตโนมัติ 18 เลขหมาย) โทรสาร : 0-2226-4020
 สาขาเชียงใหม่ : ชั้น G (ด้านในสุด) 99 หมู่ 8 ถนนพหลโยธิน ต.สุทนต์ อ.ลำลูกกา จ.ปทุมธานี
 12130 โทรศัพท์ : 0-2992-7379 โทรสาร : 0-2992-7380

www.mynpe.com E-Mail: mynpe@mynpe.com