

DCS-880MD Digital Central Controller Unit



DCS-880MD is a fully digital conference central control unit, which centralized processing and control discussion, Clear sound, hi-fidelity, Built-in telephone coupler input/output, Built-in Digital automatic feedback suppression, Support up to 60 units, Can be expanded to discussion up to 5,000 units.

DCS-880MD Supports multiple meeting for :

- Corporate meeting Rooms.
- Government meeting room & City Council Meeting.
- Education institutions.
- Courtrooms.
- Non-profit organizations.

Certifications : CE and RoHS

The DCS-880MD conforms to standard

- IEC 62321
- EN 55013 , EN 55020 , EN 60065 , EN 61000

Feature

- Fully digital conference system.
- Easy to control meeting mode and the number of speakers by the buttons on the panel.
- LCD screen displays 128 x 32 dot matrix display conference mode working status.
- The microphone can open at same time : 1,2,3,4,5,6 and full opening.
- The DCS-880MD can support 60 microphone units. And can able to support microphone up to 5000 units by power extended machine.
- The electrical load and short circuit protection function.
- The power switch turn-on/off without silent noise.
- Equipped with audio parallel output and a 6.3 jack output, conference recording outputs and background music inputs interface.
- Built-in telephone coupler input and output ports, can be used for a remote meeting.
- Built-in DAFS Function Digital automatic feedback suppression is controlled It can facility automatically eliminates acoustic feedback.
- RS232 interface can be achieved using computer software to control entire conference system function.
- Seven operational microphone modes:
 1. CHAIRMAN mode: Only chairman can speech.
 2. FIFO mode: After reaching limit number (1-6) when open new delegate microphone the first microphones will close automatic.
 3. LIFO mode: After reaching limit number (1-6) when open new delegate microphone the last delegate microphones will close automatic.
 4. LIMIT mode: Limit microphones (1-6) can open on the same time.

- Fully digital conference system.
- Built-in DAFS Function Digital automatic feedback suppression.
- Built-in telephone coupler input and output ports.
- Easy to control meeting mode and the number of speakers by the buttons on the panel.
- LCD screen displays 128 x 32 dot matrix display conference mode working status.
- The microphone can open at same time : 1,2,3,4,5,6 and full opening.
- The DCS-880MD can support 60 microphone units. And can able to support microphone up to 5000 units by power extended machine.
- The electrical load and short circuit protection function.
- The power switch turn-on/off without silent noise.
- Equipped with audio parallel output and a 6.3 jack output, conference recording outputs and background music inputs interface.
- Seven operational microphone modes:
 1. CHAIRMAN mode
 2. FIFO mode
 3. LIFO mode
 4. LIMIT mode
 5. FREE mode
 6. REQUEST mode
 7. TEST mode

Controls and Indicators



Front

- Power on/off switch.
- 1 LCD display for status information and configuration.
- 1 button (VOL+) for increase volume or select menu to the top.
- 1 button (SET) for select ok or enter to the Menu.
- 1 button (VOL-) for reduce volume or select menu to the bottom.
- 1 button (ESC) for Return or Exit

DCS-880MD Digital Central Controller Unit

Interconnections and Controls



Back

- One three-pole XLR balanced audio line output.
- 2 x RCA sockets Connector, Rec output or Aux output.
- 2 x RCA sockets Connector, Line input or Aux input.
- 3 x Circular din connectors 8P DIN panel female for loop through interconnection.
- 1 x Circular din connectors 8P DIN panel female for extension connection of conference units.
- 1 x ¼" Female panel mount Jack MIX output.
- 1 x 9-Pin female serial connector (RS232) for control entire conference system function via software computer.
- 1 x 6-Pin RJ11 female connector for input Telephone cable.
- 1 x 6-Pin RJ11 female connector for output Telephone cable.
- 1 x Button switch for DAFS on/off.
- 1 x AC input.

Specifications

Power Supply	AC 100-240V
Max Power Consumption	120W
Frequency response	30Hz-18kHz
Input impedance	LINE:50KΩ DIN:50KΩ
Output impedance	RECORD :200Ω LINE :200Ω BALANCE: 300Ω UNBALANCE: 400Ω
Signal to Noise Ratio	> 100dB @ 1KHz
Total Harmonic Distortion Ratio	< 1 % @ 1kHz
Operation temperature	0°C ~ 35°C
Storage temperature	-40°C ~ 70°C
Color	Silver
Dimensions	480x55x220 mm
Weight	4.0 Kg
Set	19 inches racks

Diagram

