

PCS-210L

www.4-acoustic.com

- Highest quality Baltic multiplex wood
- Water-resistant Polyurea coating
- Suitable for touring, rental and installation
- 1600 W program power
- 800 W AES power
- Vertical adjustment from 0° to 10° with a resolution of 1,0° per step
- Mechanical brake for easy installation and setup
- 8 Ohm Impedance
- Coverage pattern is 10°x120°

PCS-210L is a compact size, high power speaker to use in vertical line array columns up to 24 units per flight frame. The mechanical design offers a vertical adjustment from 0° to 10° with a resolution of 1,0° per step. For an easy setup of the vertical angle PCS-210L is equipped with a simple but clever mechanical brake. The entire flyware is made of high quality, extreme resilient aluminum components. This two way passive system is comprised of two 10" Neodymium woofers in dipole arrangement and two centrally mounted 1" drivers connected to an accurate calculated wave guide. The maximum SPL of a single unit is 136 dB. The coverage pattern is 10°x120° (v x h). The shock-proof and weather-resistant housing is made of best quality Baltic multiplex wood and covered with a strong, black water-resistant Polyurea coating. Four integrated handles will support an easy transport and installation. The front side of the speaker is protected by a 1,5 mm strong, black metal grill covert with black color acoustic foam. The flight frame construction allows hanging and standing installation on PCS subwoofers. The compact size and 2-way passive design guarantee a maximum of flexibility in use with our DSP system controller and DSP integrated system amplifiers.

Speci-
fication

PCS-210L

Model Name	PCS-210L
GS1 (EAN) CODE	4260318510646
System Type	2x10"/2x1" Line Array Module
Power Rating	800 W AES 1600 W program 3200 W peak
Frequency Range (+/- 3 dB)	75 Hz - 20 kHz
Coverage Pattern (hxv)	120°x10°
Sensitivity	104 dB 1w/1m
Maximum SPL	136 dB
Woofer	2 x STG-10L 350W AES, 3,0" voice coil, neodymium
Driver	2 x STG-45NB 50W AES, 1,75" voice coil, neodymium
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Housing	Baltic Birch Multiplex
Coating	Water-resistant Polyurea coating
Dimensions (h/w/d)	319x750x515 mm
Net weight	28,0 Kg





Pro Audio
Germany

PCS-210L-FFR

www.4-acoustic.com

- Scalable up to 24 units PCS-210L per flight frame
- Suitable for PCS-210L
- 4 mm strong galvanized Steel
- Shockproof black powder coating
- Support multi pick point fixing



Pro Audio
Germany

PCS-210L-FFR-L

www.4-acoustic.com

- Multi function flight frame design
- Suitable for PCS-210L hanging up to 4 pcs
- Ground stack support frame
- Shockproof black powder coating
- Support multi pick point fixing
- Snap In fixing as ground stack
- 4 mm strong galvanized Steel



Accessories

PCS-210L

Order Code	GS1 (EAN) Code	Description
PCS-210L-FFR	4260318510653	Flight Frame for PCS-210L
PCS-210L-FFR-L	4260318510660	Flight Frame Light for PCS-210L
PCS-210L-FC	4260318511414	Flight Case with wheels for 2 pcs. PCS-210L modules
KA-SP2-0.5	4260318510929	0,5 Meter speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter speaker cable 2x2,5qmm



INLINE Marketing GmbH
Bunsenstrasse 32
59229 Ahlen, Germany

Tel. +49 2382 7087-0
Fax +49 2382 7087-25
E-Mail sales@4-acoustic.com
Web www.4-acoustic.com

GERMAN
Pro Audio
Engineering

Page 2 of 2